

RG-15 Optical Rain Gauge



PRODUCT DESCRIPTION

The RG-15 Optical Rain Gauge is a rainfall measuring device intended to replace conventional tipping buckets. It uses beams of infrared light within a plastic lens about the size of a tennis ball. The round surface of the lens discourages collection of debris, and the RG-15 has no moving parts to stick, and no water-pathways to clog. The device features an open-collector output that emulates a conventional tipping bucket, as well as serial communications that provide more detailed data and allow for configuration of the device.

The RG-15 may be configured through the serial port, or optionally via DIP switches. The device is lower power to begin with, and enters micropower mode in the absence of rain. Thus, the RG-15 is well suited to solar-powered applications.

FEATURES

- Industrial-grade design: High reliability with a rugged surface, provides accurate measurements
- User friendly: Can be easily installed on weather station masts, buildings, and other infrastructures
- Maintenance-free: No debris would be generated and no clogging in the gauge
- Wide application scenarios: Can be used in various scenarios like hydrological network monitoring, irrigation control, climate studies, etc.

APPLICATION

- Smart Agriculture
- Smart City
- Climate Studies
- Hydrological Network Monitoring
- Condensation and Frost Sensing
- Irrigation Control
- Drop Detection
- Wiper Control

SPECIFICATIONS

PRODUCT MODEL

Model	RG-15
-------	-------

GENERAL PARAMETER

Parameter	Value	Connection Pins
Nominal Accuracy	±10%1	J1 Terminal J1 - Out
Input Voltage	Range 5- 15 VDC on J1 Reverse polarity protected to 50V or 3.3VDC through pin 8 on J2	J1 - V+ J1 - GND
Current Drain (Not final)	110 µA nominal. (No outputs on, dry not raining) 2-4 mA when raining	J2 Header J2 - 1 GND J2 - 2 V+ (Same as J1 V+)
Output	NPN Open Collector Output 100 mA / 80V Max	J2 - 3 OUT (Same as J1 OUT) J2 - 4 Serial OUT
Operating Temperature	-40°C to +60°C (Will not detect rain when freezing)	J2 - 5 Serial IN J2 - 6 TB IN, Bridge to ground, normally open
Output Resolution	0.01in / 0.2mm or 0.001in / 0.02mm	J2 - 7 MCLR J2 - 8 3.3V
Two Way Communication	3.3V TTL Serial (RS232)	
Supported Baud Rates	1200, 2400, 4800, 9600, 19200, 38400, 7600	